

Stile & Rail Doors - Exterior Application

Standard and environmental models are available.

Product Features and Specifications	Exterior Application
Door Styles <i>(Panel Styles may vary based on required construction)</i>	French, Traditional, Archtop (radius), Other
Panel Design <i>(Panel Styles may vary based on required construction)</i>	Square-top, Archtop (radius) panels, Eyebrow, Provence, Other
Single Doors <i>(max size listed)</i> <i>Consult factory for oversized doors.</i>	Width: 42" Height: 96" Thickness: 1 3/4", 2 1/4"
Pair Doors <i>(maximum size listed)</i> <i>(Standard Swinging, Contact Factory for D/E)</i>	Width: 84" Height: 96" Thickness: 1 3/4", 2 1/4"
Surface Types <i>Expansive veneer offerings available. Contact factory for details.</i>	<ul style="list-style-type: none"> •Wood Veneer: Standard 1/8"; Mahogany, Cherry, Walnut, Pine, Fir, White Oak •Painted: Stiles and Rails - Mahogany, Panels MDF
Default Face Dimensions <i>Contact factory for custom options.</i>	<ul style="list-style-type: none"> •Stiles: 5 1/2" •Top Rail: 5 1/2" •Bottom Rail: 10" (minimum 12" for over 36" wide) •Lock Rail: 6 1/2" •Muntins (<i>Simulated Divided Lite</i>) & Bars (<i>True Divided Lite</i>): 1 3/8" (including glass stops) •Crossrail (Intermediate): 3 5/8" •Mullions: 3 5/8"
Joinery	Cope & Stick; Doweled
Core and Panel Material	<ul style="list-style-type: none"> •Stiles: SCLC •Top Rail: Solid Lumber •Bottom Rail: Solid Lumber •Lock Rail: Solid Lumber •Mid-rails: Solid Lumber •Mullions: Solid Lumber •Louvers (Standard, False, Chevron): Solid Lumber •Rim Banded Raised Panel: MDF •Veneer Wrapped Raised Panel: N/A •Flat Panel: MDF •Paint Grade Panel / Louvers: Solid Wood
Panel Options	<ul style="list-style-type: none"> •Rim Banded Raised Panel: 1 5/8" •Veneer Wrapped Raised Panel: N/A •Flat Panel: 5/8" •V-Groove Flat Panel: 1 1/8" •V-Groove Raised Panel: 1 5/8"
Sticking Options <i>Contact factory for custom options.</i>	Ogee, Ovolo, No profile, Square, Quarter Round, Custom

Note: Doors are manufactured per the standards listed on this page. Specifications are subject to change without notice.

Stile & Rail Doors - Exterior Application

Standard and environmental models are available.

Product Features and Specifications	Exterior Application
Raised and Applied Molding	Available upon request
Glass	<p>•Standard Glass (Maximum cutout): -1/4" Tempered -5/8" Tempered insulated</p> <p>•Optional Glass Types: -Tempered: Clear, Clear Bevel, Acid Etched, Acid Etched with Clear Bevel -Laminated: Clear, White Contact factory for options and limitations.</p> <p>•Additional Options: Insulated Glass, Low E and Argon</p>
<p>Machining <i>(Typical factory machining)</i> Contact factory for more options.</p>	<ul style="list-style-type: none"> • Hinges • Cylindrical locks • Mortise locks with or without function holes • Card Locks • Exit devices • Automatic or Manual flush bolts • Concealed overhead closers / stops • Door bottoms • Electric Strikes • Viewers • Wire Raceways • EPT's
<p>Environmental Offerings <i>(available upon request)</i></p>	<ul style="list-style-type: none"> • Recycled Content • Certified Wood • Low-Emitting Materials • Carb Phase II Compliant
Acoustic Rating	N/A
Warranty	3 Year Warranty (must be factory finished)
Label Agency	N/A

Note: Doors are manufactured per the standards listed on this page. Specifications are subject to change without notice.